



Wire, Cable and Battery Accessories



voltage: rated at 60V or less
 temperature: rated at -55°C (-67°F) to 80°C (176°F)
 Specifications: Inner wires meet Sae J1128

TRAILER LIGHTING CABLE

- 19-1328 04914, 12/6-10/1 100' W,BK,Y,R,GR,BR,BL
- 19-1302 04904, 14/4 100' BK,R,BR,W
- 19-1335 04915, 14/4-10/2-12/1 100' DBL,BR,BK,DGR,R,W,Y
- 19-1303 04906, 14/6 100' R,GR,BR,W,BK,Y
- 19-1304 04908, 14/7 100' R,GR,BR,W,BK,Y,BL
- 55-0490 04900, 16/4 100' BK,R,BR,W



voltage: rated at 60V or less
 temperature: rated at -50°C (-58°F) to 105°C (221°F)
 Specifications: sae j1127

STARTER CABLE

- 55-1760 04615, 2 GA 100' BLK
- 55-1759 04614, 2 GA 100' RED
- 19-1342 04613, 2 GA 25' BLK
- 19-1330 04612, 2 GA 25' RED
- 19-1190 04609, 4 GA 100' BLK
- 19-1192 04608, 4 GA 100' RED
- 19-1311 04606, 4 GA 25' RED
- 55-6754 04603, 6 GA 100' BLK
- 55-6755 04602, 6 GA 100' RED



CABLE TIES

- 19-1425 05724, Cable Ties, Black, 5"
- 19-1426 05725, Cable Ties, Black, 7"
- 19-1427 05726, Cable Ties, Black, 11"
- 19-1455 05727, Cable Ties, Black, 14"
- 56-5763 05763, Hd Cable Ties, Black, 14.2"
- 56-5764 05764, Hd Cable Ties, Black, 24.2"



HEAT SHRINK TUBING


- 55-0406 05406, Heat Shrink Tubing 1/0-4/0 Blk
- 55-0407 05407, Heat Shrink Tubing 1/0-4/0 Red
- 55-0404 05404, Heat Shrink Tubing 1-2/0 Blk
- 55-0405 05405, Heat Shrink Tubing 1-2/0 Red
- 55-0402 05402, Heat Shrink Tubing 8-2 Blk
- 55-0403 05403, Heat Shrink Tubing 8-2 Red
- 55-8734 05447, Heat Shrk Tb 1/4" 12-18 Blk 25pk
- 55-8735 05448, Heat Shrk Tb 1/4" 12-18 Red 25pk
- 55-8729 05451, Heat Shrk Tb 1/8" 18-14 Blk 25pk
- 55-8730 05452, Heat Shrk Tb 1/8" 18-14 Red 25pk
- 55-8731 05449, Heat Shk Tb 3/16" 14-10 Blk 25pk
- 55-8733 05450, Heat Shk Tb 3/16" 14-10 Red 25pk

East Penn Manufacturing Company
 and its **Deka** brand of products,
 has been a leader in the battery and
 accessories industry since 1946.



PRIMARY WIRE (CONTINUED)

- 55-7265 02310, 18 GA 100' 80 BLK
- 55-7269 02314, 18 GA 100' 80 BLU
- 55-7268 02313, 18 GA 100' 80 BRN
- 55-7266 02311, 18 GA 100' 80 GRN
- 55-7263 02308, 18 GA 100' 80 RED
- 55-7264 02309, 18 GA 100' 80 WHT
- 55-7267 02312, 18 GA 100' 80 YEL
- 62-0565 02338, 18 GA 1000' 80 BLK
- 62-0569 02342, 18 GA 1000' 80 BLU
- 62-0568 02341, 18 GA 1000' 80 BRN
- 62-0566 02339, 18 GA 1000' 80 GRN
- 62-0563 02336, 18 GA 1000' 80 RED
- 62-0564 02337, 18 GA 1000' 80 WHT
- 62-0567 02340, 18 GA 1000' 80 YEL
- 19-0760 00395, 18 GA 40' 80 BLK 1/CD
- 55-6697 00394, 18 GA 40' 80 RED 1/CD



voltage: rated at 60V or less
 temperature: rated at -30°C (-22°F) to 105°C (221°F)
 Specifications: Inner wires meet Sae j1128

AUTO DUPLEX AND TRIPLEX WIRE

- 19-1312 03212, 12/2 100' BLK,WHT
- 19-1313 03214, 12/2 1000' BLK,WHT
- 55-1776 03219, 12/2 500' BLK,BLU W/RED JKT
- 19-1308 03206, 14/2 100' BLK,WHT
- 19-1309 03208, 14/2 100' BLK,WHT
- 62-0574 03203, 16/2 100' BLK,RED
- 62-0570 03200, 16/2 100' BLK,WHT
- 62-0576 03205, 16/2 1000' BLK,RED
- 62-0572 03202, 16/2 1000' BLK,WHT
- 19-0959 03204, 16/2 500' BLK,RED
- 62-0571 03201, 16/2 500' BLK,WHT
- 62-0577 99234, 16/2 8000' BLK,RED W/GRY JKT FR
- 62-0573 14845, 16/2 8000' BLK,WHT W/GRY JKT FR
- 62-0586 03233, 12/3 100' BLK,GRN,WHT
- 62-0588 03235, 12/3 1000' BLK,GRN,WHT
- 62-0589 14849, 12/3 3000' BLK,WHT,GRN W/GRY FR
- 62-0587 03234, 12/3 500' BLK,GRN,WHT
- 62-0582 03230, 14/3 100' BLK,GRN,WHT
- 62-0584 03232, 14/3 1000' BLK,GRN,WHT
- 62-0585 14850, 14/3 4000' BLK,WHT,GRN W/GRY FR
- 62-0583 03231, 14/3 500' BLK,GRN,WHT
- 62-0578 03227, 16/3 100' BLK,GRN,WHT
- 62-0580 03229, 16/3 1000' BLK,GRN,WHT
- 62-0579 03228, 16/3 500' BLK,GRN,WHT
- 62-0581 14851, 16/3 5000' BLK,WHT,GRN W/GRY FR



voltage: rated at 60V or less
 temperature: rated at -30°C (-22°F) to 80°C (176°F)
 Specifications: sae j1128

BONDED PARALLEL WIRE

- 19-1318 02903, 14/3 100' BRN,YEL,GRN
- 19-1320 02906, 14/4 100' WHT,BRN,YEL,GRN
- 19-0951 02908, 14/4 1000' WHT,BRN,YEL,GRN
- 55-2912 02912, 16/3 100' BRN,YEL,GRN
- 19-0953 02915, 16/4 100' WHT,BRN,YEL,GRN
- 55-9711 02917, 16/4 1000' WHT,BRN,YEL,GRN
- 55-6806 00907, 16/4 25' WHT,BRN,YEL,GRN
- 19-0954 02916, 16/4 500' WHT,BRN,YEL,GRN
- 55-7159 02941, 18/3 & 1/61 25' WHT,BRN,YEL,GRN

voltage: rated at 60V or less
 temperature: rated at 80°C (176°F)
 Specifications: sae j1128

PRIMARY WIRE

- 19-1204 02552, 8 GA 100' 80 BLK
- 19-1203 02550, 8 GA 100' 80 RED
- 19-1200 02551, 8 GA 100' 80 WHT
- 19-1211 02510, 10 GA 100' 80 BLK
- 19-1210 02508, 10 GA 100' 80 RED
- 19-0946 02512, 10 GA 100' 80 YEL
- 55-8761 02538, 10 GA 1000' 80 BLK
- 55-7081 02542, 10 GA 1000' 80 BLU
- 55-8759 02536, 10 GA 1000' 80 RED
- 55-7080 02537, 10 GA 1000' 80 WHT
- 55-9196 00499, 10 GA 8' 80 BLK 1/CD
- 55-9841 00498, 10 GA 8' 80 RED 1/CD
- 19-1219 02460, 12 GA 100' 80 BLK
- 19-1214 02464, 12 GA 100' 80 BLU
- 19-1217 02463, 12 GA 100' 80 BRN
- 19-1215 02461, 12 GA 100' 80 GRN
- 19-1218 02458, 12 GA 100' 80 RED
- 19-1212 02459, 12 GA 100' 80 WHT
- 19-1213 02462, 12 GA 100' 80 YEL
- 19-1251 02488, 12 GA 1000' 80 BLK
- 19-1247 02492, 12 GA 1000' 80 BLU
- 55-8796 02491, 12 GA 1000' 80 BRN
- 55-8772 02489, 12 GA 1000' 80 GRN
- 19-1250 02486, 12 GA 1000' 80 RED
- 19-1245 02487, 12 GA 1000' 80 WHT
- 55-8776 02490, 12 GA 1000' 80 YEL
- 55-9186 00491, 12 GA 12' 80 BLK 1/CD
- 55-9181 00490, 12 GA 12' 80 RED 1/CD
- 19-1226 02410, 14 GA 100' 80 BLK
- 19-1222 02414, 14 GA 100' 80 BLU
- 19-1224 02413, 14 GA 100' 80 BRN
- 19-1223 02411, 14 GA 100' 80 GRN
- 19-1225 02408, 14 GA 100' 80 RED
- 19-1220 02409, 14 GA 100' 80 WHT
- 19-1221 02412, 14 GA 100' 80 YEL
- 19-1258 02438, 14 GA 1000' 80 BLK
- 19-1254 02442, 14 GA 1000' 80 BLU
- 19-1256 02441, 14 GA 1000' 80 BRN
- 19-1255 02439, 14 GA 1000' 80 GRN
- 19-1257 02436, 14 GA 1000' 80 RED
- 19-1252 02437, 14 GA 1000' 80 WHT
- 19-1253 02440, 14 GA 1000' 80 YEL
- 55-9176 00483, 14 GA 20' 80 BLK 1/CD
- 55-9174 00481, 14 GA 20' 80 BLU 1/CD
- 19-0809 00484, 14 GA 20' 80 BRN 1/CD
- 55-9173 00479, 14 GA 20' 80 GRN 1/CD
- 19-0784 00482, 14 GA 20' 80 RED 1/CD
- 55-9177 00480, 14 GA 20' 80 WHT 1/CD
- 55-9172 00478, 14 GA 20' 80 YEL 1/CD
- 19-1233 02360, 16 GA 100' 80 BLK
- 19-1229 02364, 16 GA 100' 80 BLU
- 19-1231 02363, 16 GA 100' 80 BRN
- 19-1230 02361, 16 GA 100' 80 GRN
- 19-1232 02358, 16 GA 100' 80 RED
- 19-1227 02359, 16 GA 100' 80 WHT
- 19-1228 02362, 16 GA 100' 80 YEL
- 19-1266 02388, 16 GA 1000' 80 BLK
- 19-1261 02392, 16 GA 1000' 80 BLU
- 19-1264 02391, 16 GA 1000' 80 BRN
- 19-1262 02389, 16 GA 1000' 80 GRN
- 19-1265 02386, 16 GA 1000' 80 RED
- 19-1259 02387, 16 GA 1000' 80 WHT
- 19-1260 02390, 16 GA 1000' 80 YEL
- 55-9166 00475, 16 GA 28' 80 BLK 1/CD
- 55-9164 00473, 16 GA 28' 80 BLU 1/CD
- 55-9163 00399, 16 GA 28' 80 GRN 1/CD
- 55-9161 00474, 16 GA 28' 80 RED 1/CD
- 55-9167 00472, 16 GA 28' 80 WHT 1/CD
- 19-0763 00398, 16 GA 28' 80 YEL 1/CD